

3C-2V

75 Ohm CCTV coaxial Cable NO.7100903



Construction Parameters:

Inner Conductor	0.50mm BC
Dielectric	3.1mm SPE
Shield	0.14mm×6×25 BC Braid(L=26)
Jacket	5.4±0.5mmPVC
Jacket Thickness	0.08mm
Application	For Use in Longer CCTV Run Lengths

Electrical Characteristics:

Inner Conductor Resistance	The Max. at 20°C shall be <math><145\Omega/\text{km}</math>
Capacitance	69±4 pF/m
Impedance	75 ± 3 Ω
Return loss	between 5 and 1000MHz: > 20dB
Velocity of Propagation	
Sparker Test (VAC)	1



HELLOSIGNAL™
www.zion-communication.com

Mechanical and Environmental Properties


Cable bend radius	10 times the cable diameter
Operating Temp Range	-20 °C to 65°C
Cable dimensions	

Cross Section

3C-2V

Shield
0.14mm×5×24
BC Braid(L=26)

Jacket
5.4mmPVC



Dielectric
3.1mmSPE

Inner Conductor
0.50mmBC

Attenuation(20°C):

Frequency (MHZ)	Max Attenuation(dB/100ft)	Max Attenuation (dB/100m)
10		4.80
30		8.30
72		12.90
88		14.20
90		14.40
135		17.60
180		20.40
220		22.50
270		24.90
440		31.80
750		41.60
770		42.10

Order Informations:

Marking	HELLOSIGNAL 3C-2V CCTV COAXIAL CABLE 7100903 ×××M/FT
Package	Inquired Length on Reel,Pull Box,Plastic Spool,wooden Spool,pallet
Delivery time	Normally 25 days after received the deposit.
Brand	HELLOSIGNAL™ OR OEM

Online Service:

Skype	kingtone3
ICQ	246632889
Whatsapp	0086 18268009191
Email	michael@zion-communication.com



www.zion-communication.com
HANGZHOU ZION COMMUNICATION CO.,LTD