



**ELECTRICAL:**

1. Rate Voltage / Current: 250V / 10A
2. Normal Electric Strength: Between Housing ( Cover the silicone insulation Tube) and Lead, Dielectric Strength should be AC 50hz, 1500V, Last 1 mins without Blink and Breakdown.
3. Insulation Resistance: Between housing (Cover the silicone insulation Tube and Lead Insulation Resistance > 2MΩ
4. Contact Insulation between Lead ≤ 0.028Ω
5. Disconnecton Insulation Resistance: Lead to lead in disconnection, Insulation Resistance ≥ 0.2MΩ
6. Leadkage Current: ≤ 0.2mA

How to Order:

RY- 250V- 10A (TF XX)

Rated Function Temperature

Available Temperature Range 55 to 285.

REV.: 01	UNIT.: mm	SCALE.: 1:1	PAGE.: 1/1		<b>GENERAL TOLERANCE</b>		DESIGN: 黄 语 惠	DATE: 2020.02.28	DWG. NO.: YH-RY-250V-10A-001A-001	TITLE: 250V/10A, Steel Type Thermal Fuse
					X.* ± 5.0°	X. ± 0.30	CHECK: 忠 诚	DATE: 2020.03.02		
					.X* ± 3.0°	.X ± 0.25	AUDIT: 忠 诚	DATE: 2020.03.02		
					.XX* ± 2.0°	.XX ± 0.15	APPROVE: 忠 诚	DATE: 2020.03.02		
					.XXX* ± 1.0°	.XXX ± 0.10				
							PART NO.: RY-250V-10A(TF142)			