	53	*20 Glass Fuse	Specification		
Name:	5mmX20mm Glass fuse (Fast acting)		<u> </u>		FxxA250-L-5*20 (xx Means actual Current
Tube materials:	Glass				
Size:	5mm x20mm	Size:	OD= 5mm, Length = 20mm, Length of Lead 30mm		
Rating Voltage	250V	Fuse materials	Coppre line with Tin plated		
Test Standard	GB9364.2-1997	Melt Break Test	2.1		
packaging	100pcs /Box				
Product Picture	OD=0.65, if current less then 10A OD=0.80, if current bigger then 2 30 20				
Technical graph	0.01 1 10 100 1000 CURRENT IN AMPERES	0.1	TIME IN SECONDS	100	1/16A 1/10A 15/10 175A 1/4A 3/8A 1/2A 3/4A 11 1 1/2A 2A 3A 4A 5A 10A 115A 20A 25A 30A
Inspection items and requirements			Test Result		Judging
Time, current characteristics: (fast action, low breaking capacity): more than 100mA- 30A				OK	
Rating 2.1In, Max 20Min			# 44-1.15s # 46-2.18s # 47-1.86s		ОК
Rating 2.75ln, Min 50ms, Max 10s Rating 4In, Min 40ms, Max 3s			# 37-308ms # 38-316ms # 39-358ms		ОК
			# 25-122ms # 26-116ms # 27-112ms	# 26-116ms OK # 27-112ms	
Rating 10In, Max 20ms			# 04-17.0ms # 05-17.8ms # 06-18.0ms		ОК
Made by:	John Sun	Checked	Lily Zhao		Date: 2018.10.02