



REV	CONTENT	CHK	DATE
V0.0	CONTENT	ZX	2020.06.19

- NOTES:
- 1.Rating 300V 8A
  - 2.Insulation Withstands Voltage: AC2000V/MIN
  - 3.Insulation Resistance: 500MΩ or more at DC500V
  - 4.Using Temperature Range: -40°C--+105°C
  - 5."★" is the important dimension

Total Pitch Tolerances		Nominal dimension range		—	≡	—	//
in mm		in mm					
over	over	over	over	over	over	over	over
0	30	53	70	90	115	150	350
to	to	to	to	to	to	to	to
30	53	70	90	115	150	250	500
±0.18?	±0.25	±0.3	±0.35?	±0.4	±0.55?	±0.70?	±0.85
±0.20	±0.25	±0.30	±0.35	±0.40	±0.55	±0.70	±0.80
0	30	53	70	90	115	150	350
to	to	to	to	to	to	to	to
30	53	70	90	115	150	250	500
±0.18?	±0.25	±0.3	±0.35?	±0.4	±0.55?	±0.70?	±0.85

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG	ZX	DATE	SIZE	A4	SHEET/OF 1/1
CHK	DATE	SCALE	4:1	UNITS	mm
APP.	DATE	NAME	ZBF200V-XXP-X		